SMART SELF-PRIMING PUMPS “HPSm-A/AX”



TECHNICAL FEATURES

- Suitable for clean water free of abrasive particles and liquids that are not chemically aggressive to the pump materials.
- Easy to use and economical: ideal for domestic use, in particular for water distribution with small pressure sets and for the irrigation of gardens and allotments.
- Supplied complete with a flap check valve.
- Keeps the water pressure stable so that water heaters work normally.
- Install in an enclosed area, or at least sheltered from bad weather.



HPSm-A



HBPSm-A (on request)



HPSm-AX

MOTOR

- Two-pole induction motor (n = 2850 rpm)
- Insulation class B; protection IP44
- Continuous service S1
- Thermal protector
- Single-phase 220 V / 50 Hz (60 Hz on request)

WORKING CONDITION


- Liquid temperature up to 80 °C
- Ambient temperature up to 40 °C
- Total suction lift up to 9 m

MATERIALS

COMPONENT	CONSTRUCTION
Pump body	Cast iron + AISI 304 SS insert
Pump cover	Cast iron (electrophoresis) + AISI 304 SS insert
Motor housing	Aluminium
Impeller	Brass
Motor shaft	AISI 304 SS
Mechanical seal	Ceramic / Graphite

SMART SELF-PRIMING PUMPS “HPSm-A/AX”

PERFORMANCE CHART AT n = 2850 RPM



NO.	MODEL	POWER kW	POWER HP	Q (m³/h)	0	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7	3
				Q (l/min)	0	5	10	15	20	25	30	35	40	45	50
A	HPSm60-A/AX	0.37	0.5	H (m)	35	30	25	20	15.5	11	7.5	4			
B	HPSm70-A/AX	0.55	0.75	H (m)	50	45	39.5	34	28.5	23	18	13	9	5	
C	HPSm80-A/AX	0.75	1	H (m)	55	49	43	37	31.5	26	21	16	12	8	4

TECHNICAL DATA

NO.	MODEL	INLET / OUTLET (inch)	N.W. (kg)	L × W × H (mm)
A	HPSm60-A/AX	1" × 1"	7.4	275 × 227 × 277
B	HPSm70-A/AX	1" × 1"	10	292 × 240 × 300
C	HPSm80-A/AX	1" × 1"	11	292 × 240 × 300

Performance values at n = 2850 rpm, 50 Hz. Specifications are subject to change without notice.