SUBMERSIBLE SEWAGE PUMPS “V1500F~V2200F”



TECHNICAL FEATURES

- Suitable for dirty water that is not chemically aggressive to the pump materials.
- Reliable and easy to use: suitable for clearing dirty water, discharging domestic waste water and emptying collection traps containing particles up to Ø 15 mm.

MOTOR

- Two-pole induction motor (n = 2850 rpm)
- Insulation class B; protection IP68
- Continuous service S1
- Thermal protector on single-phase versions
- Single-phase 220 V / 50 Hz (60 Hz on request)
- Three-phase 380 V / 50 Hz (60 Hz on request)

WORKING CONDITION


- Maximum immersion depth 5 m
- Liquid temperature up to 35 °C
- Ambient temperature up to 40 °C

MATERIALS

COMPONENT	CONSTRUCTION
Pump body	Cast iron
Motor housing	AISI 201 SS
Impeller	Cast iron
Motor shaft	AISI 304 SS
Mechanical seal	SiC / SiC
Cable	8 m power cable with plug

SUBMERSIBLE SEWAGE PUMPS “V1500F~V2200F”

PERFORMANCE CHART AT n = 2850 RPM



NO.	MODEL	POWER kW	POWER HP	Q (m³/h)	0	6	12	18	24	30	36	42
				Q (l/min)	0	100	200	300	400	500	600	700
A	V1500F	1.5	2	H (m)	15.5	14	12.5	11	9	6.5		
B	V1500F	1.5	2	H (m)	15.5	14	12.5	11	9.5	7	4.5	1
C	V2200F	2.2	3	H (m)	18	16.5	15	13.5	10.5	6.5		
D	V2200F	2.2	3	H (m)	18	16.5	15	13.5	11	8.8	6.5	3.5

TECHNICAL DATA

NO.	MODEL	OUTLET (inch)	PARTICAL (Φ mm)	N.W. (kg)	L × W × H (mm)
B	V1500F	2"	15	25	333 × 225 × 525
B	V1500F	2½" / 3"	15	25	333 × 225 × 525
D	V2200F	2"	15	28	345 × 245 × 548
D	V2200F	2½" / 3"	15	28	345 × 245 × 548

Performance values at n = 2850 rpm, 50 Hz. Specifications are subject to change without notice.