CENTRIFUGAL PUMPS “ACm/5AM/5BM”



TECHNICAL FEATURES

- Suitable for clean water and liquids that are not chemically aggressive to the pump materials.
- Reliable and easy to use: widely used in domestic and civil applications such as water distribution with small and medium-sized pressure sets, liquid transfer, and the irrigation of gardens and allotments.
- Install in an enclosed area, or at least sheltered from bad weather.



HBCm/5AM/5BM (on request)



ACm/5AM/5BM

MOTOR

- Two-pole induction motor (n = 2850 rpm)
- Insulation class B; protection IP44
- Continuous service S1
- Thermal protector on single-phase versions
- Single-phase 220 V / 50 Hz (60 Hz on request)
- Three-phase 380 V / 50 Hz (60 Hz on request)

WORKING CONDITION


- Liquid temperature up to 60 °C
- Ambient temperature up to 40 °C
- Total suction lift up to 8 m

CENTRIFUGAL PUMPS “ACm/5AM/5BM”

MATERIALS

COMPONENT	CONSTRUCTION
Pump body	Cast iron
Pump support	Aluminium
Motor housing	Aluminium
Impeller	Brass
Motor shaft	Carbon steel, AISI 304 SS on request
Mechanical seal	Ceramic / Graphite

PERFORMANCE CHART AT n = 2850 RPM



NO.	MODEL	POWER kW	POWER HP	Q (m³/h)	0	6	9	12	15	18	21	24	27	30
				Q (l/min)	0	100	150	200	250	300	350	400	450	500
A	ACm/5BM	1.1	1.5	H (m)	19	18	18	17	16	15	13	12	9	
B	ACm/5AM	1.5	2	H (m)	21	20	19	19	18	16	15	13	11	8

TECHNICAL DATA

NO.	MODEL	INLET / OUTLET (inch)	N.W. (kg)	L × W × H (mm)
A	ACm/5BM	2" × 2"	17.5	420 × 245 × 290
B	ACm/5AM	2" × 2"	18.5	420 × 245 × 290

Performance values at n = 2850 rpm, 50 Hz. Specifications are subject to change without notice.